


SLE-BS

BS柄2枚刃エンドミル 2-Flutes End Mill with BS Shank



SKH51

外径許容差(φD) $\begin{matrix} 0 \\ -0.05 \end{matrix}$

外径 φD	柄 NO.	刃長 L c	全長 L	柄長 L 1	刃数
10	BS7	25	127	92	2
11	BS7	30	132	92	2
12	BS7	30	132	92	2
1/2	BS7	33	135	92	2
13	BS7	33	135	92	2
14	BS7	33	135	92	2
9/16	BS7	33	135	92	2
15	BS7	33	135	92	2
5/8	BS7	33	135	92	2
16	BS7	33	135	92	2
17	BS7	33	135	92	2
11/16	BS7	33	135	92	2
18	BS7	33	135	92	2
19	BS7	40	142	92	2
3/4	BS7	40	142	92	2
20	BS7	40	142	92	2
21	BS7	45	147	92	2
22	BS7	45	147	92	2
7/8	BS7	45	147	92	2
23	BS7	45	147	92	2
24	BS7	45	147	92	2
25	BS7	45	147	92	2
25.4	BS7	45	147	92	2
26	BS7	45	147	92	2
27	BS7	45	147	92	2
28	BS7	45	147	92	2
1-1/8	BS7	45	147	92	2
29	BS7	45	147	92	2
30	BS7	45	147	92	2
31	BS7	45	147	92	2
32	BS7	50	154	92	2
20	BS9	45	178	120	2
21	BS9	45	178	120	2
22	BS9	45	178	120	2
23	BS9	45	178	120	2
24	BS9	45	178	120	2
25	BS9	45	178	120	2
25.4	BS9	45	178	120	2
26	BS9	45	178	120	2
27	BS9	45	178	120	2
28	BS9	45	178	120	2
29	BS9	45	178	120	2
30	BS9	45	178	120	2

被削材種 型番	鋳物	炭素鋼	合金鋼	工具鋼	調質鋼	ステンレス鋼	アルミ合金	銅合金	チタン合金	耐熱合金
	FC、FCD	S45C	SCM	SKD	NAK、HPM	SUS	Al	Cu	Ti6Al4V	インコネル
硬度	~300HB	~200HB	~250HB	~35HRC	~45HRC	~35HRC				
SLE-BS	○	○					○			

シャンク部形状 P.321

SLE-BS

BS柄2枚刃エンドミル 2-Flutes End Mill with BS Shank

外径 φ D	柄 N O.	刃長 L c	全長 L	柄長 L 1	刃数
31	BS9	50	183	120	2
1-1/4	BS9	50	183	120	2
32	BS9	50	183	120	2
33	BS9	50	183	120	2
34	BS9	50	183	120	2
1-3/8	BS9	50	183	120	2
35	BS9	50	183	120	2
36	BS9	53	186	120	2
37	BS9	53	186	120	2
38	BS9	53	186	120	2
1-1/2	BS9	55	190	120	2
39	BS9	55	190	120	2
40	BS9	55	190	120	2
41	BS9	55	190	120	2
42	BS9	55	190	120	2
43	BS9	55	190	120	2
44	BS9	60	195	120	2
45	BS9	60	195	120	2
46	BS9	60	195	120	2
47	BS9	63	198	120	2
48	BS9	63	198	120	2
49	BS9	65	200	120	2
50	BS9	65	200	120	2
50.8	BS9	65	200	120	2
51	BS9	65	200	120	2
52	BS9	65	200	120	2
53	BS9	65	200	120	2
54	BS9	65	200	120	2
55	BS9	65	200	120	2
56	BS9	65	200	120	2
57	BS9	65	200	120	2
58	BS9	65	200	120	2
59	BS9	65	200	120	2
60	BS9	70	205	120	2
62	BS9	70	205	120	2
63	BS9	70	205	120	2
64	BS9	70	205	120	2
65	BS9	75	210	120	2
68	BS9	75	210	120	2
70	BS9	75	210	120	2
75	BS9	85	220	120	2
80	BS9	90	225	120	2