

# RC

## ラックカッター Rack Type Cutter



SKH56

モジュールピッチ	圧力角	外径	刃幅	穴径	刃数
MP 0.5	20°	75	5	25.4	12
MP 0.75	20°	75	5	25.4	12
MP 0.8	20°	75	5	25.4	12
MP 1	20°	75	5	25.4	12
MP 1	20°	100	5	25.4	16
MP 1	20°	125	5	25.4	14
MP 1.25	20°	75	4.8	25.4	12
MP 1.25	20°	100	4.8	25.4	16
MP 1.5	20°	75	5	25.4	12
MP 1.5	20°	100	5	25.4	16
MP 1.75	20°	75	5	25.4	12
MP 1.75	20°	100	5	25.4	16
MP 2	20°	75	5.5	25.4	12
MP 2	20°	100	5.5	25.4	16
MP 2	20°	125	5.5	25.4	14
MP 2	20°	125	5.5	31.75	14
MP 2.5	20°	75	7	25.4	12
MP 2.5	20°	100	7	25.4	14
MP 2.5	20°	125	7	25.4	14
MP 2.5	20°	125	7	31.75	14
MP 3	20°	75	9	25.4	10
MP 3	20°	100	9	25.4	12
MP 3	20°	125	9	25.4	14
MP 3	20°	125	9	31.75	14
MP 3.5	20°	100	10.2	25.4	12
MP 3.5	20°	125	10.2	31.75	14
MP 4	20°	100	11.5	25.4	12
MP 4	20°	125	11.5	31.75	12
MP 5	20°	100	13.9	25.4	12
MP 5	20°	125	13.9	31.75	12
MP 6	20°	100	17.5	25.4	10

被削材種 型番	鋳物	炭素鋼	合金鋼	工具鋼	調質鋼	ステンレス鋼	アルミ合金	銅合金	チタン合金	耐熱合金
	FC、FCD	S45C	SCM	SKD	NAK、HPM	SUS	Al	Cu	Ti6Al4V	インコネル
RC	○	○	○			△	○	○		

切削条件 P. 297 キー溝形状 P. 305

# RC

## ラックカッター

Rack Type Cutter

モジュールピッチ	圧力角	外径	刃幅	穴径	刃数
MP 6	20°	125	17.5	31.75	12
MP 7	20°	125	19	31.75	10

ダイヤメトラルピッチ	圧力角	外径	刃幅	穴径	刃数
DP 10	14.5°	100	6.5	25.4	14
DP 8	14.5°	100	8	25.4	12
DP 6	14.5°	100	10.5	25.4	12
DP 5	14.5°	100	12.8	25.4	12
DP 4	14.5°	125	15.5	31.75	12